

# Petrol or Diesel engine driven hydraulic Sets Co-axial Version

▼ Petrol or Diesel engine driven hydraulic sets GHT 2S CX-GHT 3S CX- GHT4S CX



Petrol or diesel engine driven hydraulic sets. The most reliable alternative when electricity is unavailable

MODELS	CHARACTERISTICS
GHT2S CX	2 stage pump, distributor valve permits simultaneous 2 tool operation, with a high flow on each distributor valve.
GHT3S CX	2 stage pump, distributor valve permits simultaneous 3 tool operation, with a high flow on each distributor valve.
GHT4S CX	2 stage pump, distributor valve permits simultaneous 2 tool operation, and connection of 4 tools, with a high flow on each distributor.

#### OPTIONS

Supports spreader tool,  
With carrying handle Ref: **SO**  
With small retractable wheels Ref: **RE**

CHARACTERISTICS	GHT2S CX	GHT3S CX	GHT4S CX
Engine power output	6 HP	6 HP	6 HP
Oil capacity	8 L	8 L	8 L
1 <sup>st</sup> stage flow at 150 bar	2 x 3,2 L/mn	3 x 3,2 L/mn	2 x 3,2 L/mn
2 <sup>nd</sup> stage flow at 700 bar	2 x 0,6 L/mn	3 x 0,8 L/mn	2 x 0,6L/mn
Dimensions L x w x d (mm)	525 x 355 x 505	525 x 355 x 505	525 x 355 x 505
Weight	43.3 kg	46.8 kg	45.3 kg
Compliance Standards <b>EN 13204</b>	MTO	MTO	MTO

Powerful, Lightweight and Reliable in Rescue Operations